

Applicant: Vilho Nissinen et al.
PCT App. No.: PCTFI03/00022

Remarks

Claims 7–16 remain pending in the application.

Applicant believes that no new matter has been added by these amendments and that the application, as amended, is ready for examination. Favorable action thereon is respectfully solicited.

Respectfully submitted,



Patrick J. G. Stiennon, Reg. No. 341134
Attorney for Applicant
P.O. Box 1667
Madison, Wisconsin 53701-1667
(608) 250-4870
Amdt1.app

10/501607

DT04 Rec'd PCT/PTO 14 JUL 2004

In The United States Patent And Trademark Office

Applicant: Vilho Nissinen et al.

Date: July 14, 2004

Date Filed: Simultaneously herewith

Docket No.: BERGPAT-6


PCT App. No.: PCT/FI03/00022

For: Nozzle Array

Certificate of Express Mailing

I hereby certify that this document is being deposited with
the United States Postal Service "Express Mail Post Office to
Addressee" service under 35 C.F.R. §1.10
on July 14, 2004

with Mailing Label No. EV 447 345 481 US
and is addressed to the Commissioner for Patents, P.O. Box
1450, Alexandria, VA 22313-1450



Signature

Patrick J.G. Stiennon, Reg. No. 34934

Name of applicant, assignee or Registered Representative

Marked Up Copy of Substitute Specification under 37 C.F.R. 1.125(b)(2)

[NOZZLE ARRAY

Technological background

]

TITLE OF THE INVENTION

Nozzle Array

CROSS REFERENCES TO RELATED APPLICATIONS

[0001] This application is a U.S. national stage application of International App. No. PCT/FI03/00022, filed Jan. 14, 2003, and claims priority on Finnish App. No. 20020073, filed Jan. 15, 2002.

**STATEMENT AS TO RIGHTS TO INVENTIONS MADE UNDER
FEDERALLY SPONSORED RESEARCH AND DEVELOPMENT**

[0002] Not applicable.

BACKGROUND OF THE INVENTION

[0003] The invention relates to the coating of a mobile web-like material with high-pressure spraying techniques and is directed to the nozzle array used in such coating. The invention is especially applicable to paper coating.

5 **[0004]** In paper coating, a liquid coating mixture intended especially to improve printability is applied to the paper surface. Presses, blade applicators and film transfer devices are conventionally used for this purpose. When an increase in the drive rate is called for or papers with continually decreasing thickness are coated, these techniques are difficult to implement reliably in the practice.

10 **[0005]** Spray coating has appeared as one of the most recent coating techniques. It has the particular advantage of not requiring any mechanical coating means in contact with the web, such as an abrasive blade or a rotating rod. The spray technique called high[-]-pressure spray technique has proved particularly promising; it comprises driving merely a coating mixture without any gaseous medium under
15 high pressure through a nozzle with a small hole, so that the mixture is atomi[s]zed into small droplets. The pressure may be e.g. 1 [...] to 200 MPa and the nozzle opening area e.g. 0.02[...] to 0.5 mm². A typical maximum droplet size is about 100 µm. Such an apparatus comprises a nozzle array with one or more nozzle rows consisting of several nozzles in the transverse direction of the web. The nozzles are
20 disposed so as to provide a coating jet on the web that covers the web as evenly as possible. Then the jets generated by adjacent nozzles in a nozzle row suitably overlap at their edges. The coating mixture is distributed under the same pressure from one single feed pipe to each nozzle. This allows the flow of only the nozzles fed together to be adjusted by varying the pressure, the concentration or the
25 viscosity. The jet shape provided by the nozzles depends on the shape of the nozzle opening. The general aim is to provide a jet having a larger width in the transverse direction of the web than in its longitudinal direction. The nozzle opening is then accordingly oval.

[0006] Paper coating by spraying is described e.g. in the publications FI B 108061 (corresponding to WO 9717036) and Nissinen V, OptiSpray, the New Low Impact Paper Coating Technology, OptiSpray Coating and Sizing Conference, Finland, 15 March 2001.

5

[

General description of the invention

A nozzle array as defined in claim 1 has now been invented]

SUMMARY OF THE INVENTION

[0007] The nozzle array of this invention is for use in coating of a web-like material. [The other claims describe some preferred embodiments of the invention.

5]It has now been found that deviation in the dimensions of the nozzle openings has a substantial impact both on the flow passing through the nozzle (yield) and on the jet shape. This results in a corresponding deviation of the coating formed on the web. Accordingly, it has been found that classifying the nozzles in advance on the basis of a variable correlating with the yield deviation can diminish the yield deviation of the
10 nozzle array. The nozzles are classified so as to keep the deviation of the variable from the mean within the array under the permissible quality requirement. The requirement may be e.g. under $[\pm 5\%]_{\pm 5\%}$, such as under $[\pm 2\%]_{\pm 2\%}$.

[0008] The nozzle variable to be measured may be especially the nozzle opening area. The area can be determined especially by optical methods. The determination
15 may e.g. comprise leading a light beam, such as a laser beam, to the opening, and measuring the portion of the beam retained by the opening. The area can also be directly obtained e.g. as pixels on the image surface of a CCD camera. Instead of the area, the width and the length of the opening can be determined, using their product as a variable. These can also be optically determined using a microscope, for
20 instance. Optical measuring methods are also easy to automate.

[0009] With the nozzles classified as described above, the nozzle array yields a coating distribution on the web that is as even as possible and also remains as even as possible as the nozzles wear. The coating can be achieved with the desired thickness within each array by altering the feed values whenever necessary. The
25 classification described here is considerably more rapid and simple than classification based directly on flow measurements of the nozzles. Used nozzles can be returned and reclassified.

[0010] The invention is applicable e.g. to the classification of nozzles to be used for coating papers such as printing papers or cardboards. A classified nozzle array yields a coating of optimally even quality.

BRIEF DESCRIPTION OF THE DRAWINGS

~~{Description of}~~**[0011]** ~~{the drawings}~~

~~{~~Some embodiments of the invention are described in detail below. The accompanying drawings pertain to the description.

5 **[0012]** Figure 1 shows the distribution of the yield and fan width of an unclassified nozzle array.

[0013] Figure 2 shows the change in the yield deviation of a nozzle array as the nozzles wear.

10 **[0014]** Figure 3 shows a typical deviation of the yield of a nozzle array and its classification in accordance with the invention.

[0015] Figure 4 shows optical measurement of the nozzle area.

[0016] Figure 5 shows the position of the two outermost nozzles in the nozzle array and the distribution of the coating achieved with these.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

~~{Detailed description}[0017] {of} {some} {embodiments of the invention}~~

]The manufacturing processes used by nozzle manufacturers are inaccurate.

Manufacturers report a volume flow variation of the order of ~~[$\pm 5\%$]~~ $\pm 5\%$ at the most
5 for the nozzles. In the practice, this signifies that there may be a 10% variation in the
coating amount profile. However, practical observations show that nozzles taken
from a manufacturing batch of nozzles of the same nominal size may have a yield
deviation of over ~~[$\pm 10\%$]~~ $\pm 10\%$ from the determined mean yield.

[0018] The inventors examined the mass flow provided by each nozzle in a typical
10 batch of 36 nozzles and the width of the jet fan using water under a pressure of 100
bars. The nominal diameter of the nozzles was 0.3 mm. The results are shown in
~~[table]~~figure 1. The bars show the yield, and the curve shows the width of the jet
fan.

[0019] It was also observed that, as the nozzles wear, the yield deviation tends to
15 increase further. In fact, coating mixtures often contain solid substances, such as
pigments, which accelerate wear. This issue was studied on a batch of nine nozzles
by spraying a coating paste containing calcium carbonate and by monitoring the
change in the volume flow deviation in the course of the operating time of the
nozzles. The results are shown in ~~[table]~~figure 2.

20 [0020] Consequently, it is of paramount importance that each nozzle in a nozzle
array has the same initial yield with adequate accuracy. In this manner, a coating of
optimally even quality is obtained.

[0021] For classifying the nozzles, a variable correlating with the yield is selected,
which is determined for each nozzle. In terms of flow rate techniques, the nozzle
25 opening area shows the most exact correlation with the flow. A satisfactory result is
also obtained by measuring the diameter of the flow opening at one or more points.

In the case of an oval opening, for instance, the width and the height can be determined. When these variables of the nozzle are substantially mutually equal, the mutual yields will also be equal.

[0022] Only nozzles having a deviation of the determined variable lower than the allowable nominal deviation are mounted in the same nozzle array. The permissible limit may be e.g. $[\pm 2\%] \pm 2\%$.

[0023] Figure 3 shows a typical deviation of the flow rate of a nozzle array, which has been divided into acceptable part arrays.

[0024] One way of classifying nozzles is to measure with a microscope the width and height of the nozzle opening and to use the product of these as a classification variable. A 100-fold magnifying microscope achieves 0.001 mm precision. ~~[The enclosed table]~~ **Table 1** shows the dimensions of the holes of a batch of 10 nozzles and the corresponding mass flow. The mass flow was obtained by spraying water under a pressure of 100 bars for 2 minutes into a vessel and by weighing the water amount.

{

Table 1

Nozzle no	Width/mm	Length/mm	Length*width/mm ²	Mass flow/g/s
1	0.530	0.240	0.1272	12.6
2	0.525	0.235	0.1234	12.2
3	0.515	0.230	0.1185	11.8
4	0.515	0.230	0.1185	11.8
5	0.520	0.240	0.1248	12.4
6	0.515	0.235	0.1210	12.2
7	0.520	0.230	0.1196	12.0
8	0.500	0.225	0.1125	11.2
9	0.530	0.223	0.1182	11.6
10	0.515	0.230	0.1185	11.8

[0025] The width of an oval nozzle opening multiplied with its height is naturally greater than the opening area, but correlates perfectly well with the mass flow.

[0026] The nozzle opening area can be determined with high precision using e.g. the arrangement of figure 4. In this, a laser beam 3 having a diameter larger than the opening is taken from a laser source 1 to the opening of the nozzle 2. Having passed through the opening, the laser beam 4 is determined with a detector 5. The control and computing unit 6 calculates the difference between the laser beams, and using this as a basis, the opening area and also the main dimensions are calculated if desired. The results can be shown on a display. Such measuring apparatuses are commercially available (e.g. Keyence).

[0027] Optical measuring of the kind described above can also easily be automated.

[0028] Figure 5 shows the jet patterns 7.1 and 7.2 formed by fan-shaped jets of the two outermost nozzles 2.1 and 2.2 in a nozzle array and the weight distribution 8 of the formed coating. The jet edges are adequately overlapped in the intermediate area 9, so that the amount of coating becomes constant also in the area between the nozzles. When the nozzles have been classified in advance in accordance with the invention, the weight distribution will be optimally even across the entire web.

(57) Abstract

~~The invention relates to a~~

ABSTRACT OF THE DISCLOSURE

A nozzle array for use in the coating of a mobile web-like material~~[, comprising]~~
5 **has** a plurality of high-pressure nozzles (2.1, 2.2) in the transverse direction of the web. The nozzles (2.1, 2.2) have been classified by a variable acting on the flow so that the deviation of the variable within the array is smaller than a pre-set value. The yield of each nozzle being the same with optimal precision, an optimally even coating is achieved on the web.